

DIMENSIONES

d	D3	D2	D1	L1	L2
10	22.5	17.0	21.0	14.5	6.6
12	25.0	19.0	23.0	15.0	6.6
14	28.5	21.0	25.0	17.0	6.6
15	28.5	-	-	17.0	-
16	28.5	23.0	27.0	17.0	6.6
18	32.0	25.0	33.0	19.5	7.5
19	37.0	-	-	21.5	-
20	37.0	29.0	35.0	21.5	7.5
22	37.0	31.0	37.0	21.5	7.5
24	42.5	33.0	39.0	22.5	7.5
25	42.5	34.0	40.0	23.0	7.5
28	49.0	37.0	43.0	26.5	7.5
30	49.0	39.0	45.0	26.5	7.5
32	53.5	42.0	48.0	27.5	7.5
33	53.5	42.0	48.0	27.5	7.5
35	57.0	44.0	50.0	28.5	7.5
38	59.0	49.0	56.0	30.0	9.0
40	62.0	51.0	58.0	30.0	9.0
42	65.5	-	-	30.0	-
43	65.5	54.0	61.0	30.0	9.0
45	68.0	56.0	63.0	30.0	9.0
48	70.5	59.0	66.0	30.5	9.0
50	74.0	62.0	70.0	30.5	9.5
53	78.5	65.0	73.0	33.0	11.0
55	81.0	67.0	75.0	35.0	11.0
58	85.5	70.0	78.0	37.0	11.0
60	88.5	72.0	80.0	38.0	11.0
65	93.5	77.0	85.0	40.0	11.0
68	96.5	81.0	90.0	40.0	11.3
70	99.5	83.0	92.0	40.0	11.3
75	107.0	88.0	97.0	40.0	11.3
80	112.0	95.0	105.0	40.0	12.0
85	120.0	100.0	110.0	41.0	14.0
90	127.0	105.0	115.0	45.0	14.0
95	132.0	110.0	120.0	46.0	14.0
100	137.0	115.0	125.0	47.0	14.0

NOTA: Todas las medidas son en milímetros.



CARACTERÍSTICAS	
Especificaciones	1.2 MP a 10m/s -30° C - 200° C
Cara Estacionaria	Cerámica / SIC / TC
Cara Rotativa	Carbón / SIC / TC
Sello Secundario	NBR / EPDM / VITON
Resorte y otras Partes	S.S / SUS 304 / SUS 316

